



**Model
Timo
SlimLiner
LED
DIRECT / INDIRECT**



- Sleek Compact Profile
- Latest in LED Technology
- Aluminum extruded housing
- Dimming Compatible 0-10V
- Sure Seal Powder Coat
- Natatorium Rated

Project _____

Notes _____

- Applications:**
- Indoor/Outdoor • Offices • Schools
 - Residential • Lobby

For other custom options contact Voigt.
Example: T-325, 750L,M

fixture Series	LED	optics	lens	suspension	length	finish	voltage	options
Timo Slimliner	750lm-4100k	DI	HPFR	SM	4'	WH	UNIV	BAT-1
T-325-	Lumens per foot 450 750 ID-Indirect Lumens- 450/750 only Color Temp 3k, 35k, 4k, 5k Specify after designated lumen package.	DI – Direct Only DI/ID- Direct Indirect Note: Indirect Available on minimum 4' length, and only 2' with maximum 1' aperture for ID	HPFR- High Performance Frost LV- Parabolic Louver	SM-Surface Mount AC-Air Craft- specify length in inches for cable. SC-Swivel canopy- specify Stem length in inches RC-Rigid Canopy- specify stem length in inches DWM-flush Wall Mount WM-Wall mount w/STD 1" Standoff-(if other then specify) REC-Recess Direct Only	Specify length desired for fixture	WH-White DB-Dark Bonze BL-Black SIL-Silver For other color options contact Voigt	UNIV— 120/277	Dimm-0-10vSTD compatible Driver w/Universal voltage BAT-1-LED- Remote Battery Back UP(specify voltage) MS-Motion Sensor OCC-Occupancy Sensor CRL-Continuous Run (specify length) WL-Wet Rating (available Direct Model only) ADJSC-Field Adjustable Swivel Canopy ADJRC-Field Adjustable Rigid Canopy

TIMO SLIMLINER LED

- Sleek Compact Profile
- Latest in LED Technology
- Aluminum extruded housing
- Dimming Compatible 0-10V
- Sure Seal Powder Coat
- Natatorium Rated

Applications:

- Indoor/Outdoor • Offices • Schools
- Residential • Lobby

